

IN THE CLAIMS

Please cancel claims 1-8 without prejudice.

Please enter the following new claims 9 - 16.

9. A system for controlled operation of a device propelled by electric motors, said system having:

at least two drive wheels mounted in an axially opposed manner;

an independent electric motor for propelling each drive wheel;

a first and a second push and pull element;

an independent control means for each independent electric motor, each control means having:

a plurality of sensor means;

an independent power amplifier;

the sensor means:

detecting a mechanical force of pushing and pulling applied to the push and pull elements by a user;

transforming said mechanical force into electric signals indicating degree and direction of the mechanical force;

capable of being operated separately so as to power each drive wheel selectively;

the independent power amplifier:

amplifying the electric signals produced by the sensor means;

supplying electric power to the electric motor;

the electric signals being amplified in accordance with an amplification factor as a function of the device weight;

each drive wheel being propelled in accordance with a torque corresponding to movement ordered by the sensor means;

wherein:

B2  
each power amplifier is provided with a feedback circuit for comparing, by means of a comparator means, a true value of an electric current fed to the electric motor with a pre-established nominal value of an electric current needed to achieve movement of each drive wheel, error signals being generated from differences detected between the true value and the pre-established value, the electric input signals to the power amplifier being altered by the error signals, so as to supply the necessary power to the electric motor so that needed torque for producing movement is generated by the electric motor.

10. A system according to claim 9 wherein each one of the control means further comprises a first preamplifier means for amplifying electric signals produced by the sensor means.

11. A system according to claim 9 wherein the feedback circuit further comprises a second preamplifier means for amplifying error signals.

12. A system according to claim 9 further comprising a connecting element for coupling the push and pull elements, so as to allow a user to act selectively on the first or the second push and pull element by pushing or pulling said connecting element.

13. A system according to claim 12, wherein  
the push and pull elements,  
the force sensors, and  
the connecting element,  
are arranged so as to form handle.

14. A system according to claim 12 wherein:

B2  
the push and pull elements comprise bands having a first extremity and a second extremity, the  
first extremity being coupled to the connecting element and the second extremity being held  
immobile in fasteners;  
the force sensors comprise extension-measuring gauges arranged on the bands for detecting a  
deformation on each band when the connecting element is pushed or pulled.

15. A system according to claim 9 wherein the at least two drive wheels comprises two drive  
wheels.

16. A system according to claim 9 wherein the device propelled is a mobile X-ray unit.

---